



AUTOMOTIVE WINDOW FILMS

PRODUCT	% VISIBLE LIGHT TRANSMISSION (VLT)	%TOTAL SOLAR ENERGY REJECTION (TSER)	% VISIBLE LIGHT REFLECTANCE (VLR)	% UV REJECTION	THICKNESS (Mils)
CarbonXP™ Series (Black)					
CXP 80	80	44	7	>99	1.5
CXP 70	65	44	7	>99	1.5
CXP 55	53	48	7	>99	1.5
CXP 45	40	50	7	>99	1.5
CXP 35	33	53	6	>99	1.5
CXP 18	16	56	6	>99	1.5
CXP 5	6	59	5	>99	1.5
Carbon™ Series (Black)					
Carbon 70	70	28	5	99	1.5
Carbon 55	60	32	5	99	1.5
Carbon 45	45	40	5	99	1.5
Carbon 38	42	41	5	99	1.5
Carbon 35	35	42	5	99	1.5
Carbon 25	24	43	5	99	1.5
Carbon 18	18	44	5	99	1.5
Carbon 5	6	50	5	99	1.5
InfinityOP™ Series (Neutral)					
INF 65	65	40	8	99	1.5
INF 50	53	40	10	99	1.5
INF 35	33	55	11	99	1.5
INF 20	21	60	11	99	1.5
INF 10	11	67	15	99	1.5
High Performance™ Series (Charcoal, Blue, Bronze)					
HP 55	60	33	8	99	1.5
HP 50	52	35	8	99	1.5
HP 40	44	43	8	99	1.5
HP 35	38	49	8	99	1.5
HP 30	30	51	8	99	1.5
HP 20	22	54	8	99	1.5
HP 15	15	56	8	99	1.5
HP 5	5	58	8	99	1.5
HP 50 Blue	55	34	8	99	1.5
HP 40 Bronze	40	45	8	99	1.5
HP 18 Bronze	18	60	8	99	1.5
Standard Pro™ Series (Charcoal)					
STD Pro 50	62	29	8	99	1.5
STD Pro 35	35	36	8	99	1.5
STD Pro 20	20	39	8	99	1.5
STD Pro 15	15	43	8	99	1.5
STD Pro 5	5	46	7	99	1.5